

KLAMATH R BL IRON GATE DAM CA
 DISCHARGE, CUBIC FEET PER SECOND; TEMPERATURE, WATER (DEG. C); PH, WATER, WHOLE, FIELD, STANDARD UNITS;
 OXYGEN DISSOLVED (MG/L);SPECIFIC CONDUCTANCE (MICROSIEMENS/CM AT 25 DEG. C); TEMPERATURE, AIR, DEGREES FAHRENHEIT
 START="19991001" END "20000930"

DATE	DC MEAN	BOR MIN	WT MIN	WT MAX	pH MIN	pH MAX	DO MIN	DO MAX	CON MIN	CON MAX	AT MIN	AT MAX	PRECIP	ACCUM PRECIP
10/1/1999	1370												0.00	0.00
10/2/1999	1380												0.00	0.00
10/3/1999	1380												0.00	0.00
10/4/1999	1380												0.00	0.00
10/5/1999	1380												0.00	0.00
10/6/1999	1390												0.14	0.14
10/7/1999	1390												0.00	0.14
10/8/1999	1390												0.00	0.14
10/9/1999	1390												0.00	0.14
10/10/1999	1390												0.00	0.14
10/11/1999	1390												0.00	0.14
10/12/1999	1390												0.00	0.14
10/13/1999	1390												0.00	0.14
10/14/1999	1390												0.00	0.14
10/15/1999	1390												0.00	0.14
10/16/1999	1380												0.00	0.14
10/17/1999	1380												0.00	0.14
10/18/1999	1380												0.00	0.14
10/19/1999	1380												0.00	0.14
10/20/1999	1380												0.00	0.14
10/21/1999	1380												0.00	0.14
10/22/1999	1380												0.00	0.14
10/23/1999	1380													0.14
10/24/1999	1380													0.14
10/25/1999	1390													0.14
10/26/1999	1390												0.03	0.17
10/27/1999	1370												0.07	0.24
10/28/1999	1520												0.25	0.49
10/29/1999	1820												0.00	0.49
10/30/1999	1820												0.00	0.49
10/31/1999	1820												0.00	0.49
11/1/1999	1820												0.00	0.49
11/2/1999	1820												0.00	0.49
11/3/1999	1820												0.00	0.49
11/4/1999	1830												0.00	0.49
11/5/1999	1830												0.00	0.49
11/6/1999	1830												0.00	0.49
11/7/1999	1830												0.00	0.49
11/8/1999	1830												0.00	0.49
11/9/1999	1830												0.00	0.49
11/10/1999	1830												0.16	0.65
11/11/1999	1830												0.00	0.65
11/12/1999	1820												0.00	0.65
11/13/1999	1820												0.00	0.65
11/14/1999	1820												0.00	0.65
11/15/1999	1820												0.00	0.65
11/16/1999	1820												0.19	0.84
11/17/1999	1820												0.22	1.06
11/18/1999	1820												0.00	1.06
11/19/1999	1820												0.03	1.09
11/20/1999	1820													1.09
11/21/1999	1820													1.09
11/22/1999	1820												0.02	1.11
11/23/1999	1810												0.07	1.18
11/24/1999	1820												0.01	1.19
11/25/1999	1820													1.19
11/26/1999	1820													1.19
11/27/1999	1820													1.19
11/28/1999	1810													1.19
11/29/1999	1810												0.08	1.27
11/30/1999	1830												0.33	1.60
12/1/1999	1830												0.08	1.68
12/2/1999	1830												0.22	1.90
12/3/1999	1830												0.00	1.90
12/4/1999	1820													1.90
12/5/1999	1820													1.90
12/6/1999	1820												0.08	1.98
12/7/1999	1820												0.12	2.10
12/8/1999	1810												0.15	2.25
12/9/1999	1810												0.02	2.27

KLAMATH R BL IRON GATE DAM CA
DISCHARGE, CUBIC FEET PER SECOND; TEMPERATURE, WATER (DEG. C); PH, WATER, WHOLE, FIELD, STANDARD UNITS;
OXYGEN DISSOLVED (MG/L);SPECIFIC CONDUCTANCE (MICROSIEMENS/CM AT 25 DEG. C); TEMPERATURE, AIR, DEGREES FAHRENHEIT
START="19991001" END "20000930"

DATE	DC	MEAN	BOR	MIN	WT	MIN	WT	MAX	pH	MIN	pH	MAX	DO	MIN	DO	MAX	CON	MIN	CON	MAX	AT	MIN	AT	MAX	PRECIP	ACCUM	PRECIP
12/10/1999		1810																							0.00	2.27	
12/11/1999		1810																									2.27
12/12/1999		1810																									2.27
12/13/1999		1820																									2.27
12/14/1999		1820																									2.27
12/15/1999		1820																									2.27
12/16/1999		1820			6.0		6.2		7.2		7.6					144		146			29		51		0.00	2.27	
12/17/1999		1820			5.9		6.1		7.2		7.5					144		144			28		49		0.00	2.27	
12/18/1999		1810			5.9		6.3		7.2		7.5					144		144			27		48		0.00	2.27	
12/19/1999		1810			5.6		6.0		7.4		7.5					143		145			24		55		0.00	2.27	
12/20/1999		1820			5.3		5.6		7.4		7.5					144		144			22		56		0.00	2.27	
12/21/1999		1820			5.1		5.5		7.4		7.5					143		144			20		57		0.00	2.27	
12/22/1999		1820			4.9		5.3		7.4		7.4					143		144			20		56		0.00	2.27	
12/23/1999		1810			4.8		5.1		7.4		7.4					143		144			18		55		0.00	2.27	
12/24/1999		1820			4.6		5.0		7.3		7.4					143		143			17		54		0.00	2.27	
12/25/1999		1830			4.5		4.9		7.3		7.4					143		144			18		54		0.00	2.27	
12/26/1999		1830			4.4		4.8		7.4		7.4					143		144			16		55		0.00	2.27	
12/27/1999		1830			4.3		4.7		7.4		7.4					143		144			17		56		0.00	2.27	
12/28/1999		1830			4.2		4.6		7.4		7.4					142		144			17		54		0.00	2.27	
12/29/1999		1830			4.1		4.4		7.4		7.4					143		152			16		51		0.00	2.27	
12/30/1999		1830			4.0		4.4		7.4		7.4					142		152			15		51		0.00	2.27	
12/31/1999		1880			4.0		4.4		7.4		7.4					142		143			16		49		0.00	2.27	
1/1/2000		1930			4.0		4.3		7.3		7.5					143		149			17		35		0.01	2.28	
1/2/2000		1830			3.9		4.3		7.4		7.5					148		151			18		41		0.01	2.29	
1/3/2000		1830			4.2		4.5		7.4		7.5					146		149			32		43		0.00	2.29	
1/4/2000		1830			4.2		4.5		7.4		7.5					142		146			30		52		0.02	2.31	
1/5/2000		1830			4.0		4.4		7.4		7.4					142		143			21		49		0.00	2.31	
1/6/2000		1830			3.8		4.1		7.4		7.4					142		143			19		38		0.00	2.31	
1/7/2000		1830			3.9		4.2		7.4		7.5					142		142			27		49		0.00	2.31	
1/8/2000		1830			4.0		4.3		7.4		7.5					142		143			27		53		0.00	2.31	
1/9/2000		1830			4.0		4.2		7.4		7.4					142		143			30		44		0.02	2.33	
1/10/2000		1840			4.1		4.1		7.4		7.4					136		148			36		44		0.26	2.59	
1/11/2000		1960																			32		47		0.14	2.73	
1/12/2000		3040																			26		43		0.00	2.73	
1/13/2000		3320																			33		48		0.08	2.81	
1/14/2000		4100																			38		43		0.19	3.00	
1/15/2000		3620																			37		51		0.10	3.10	
1/16/2000		3380			4.0		4.3		7.7		7.8					151		158			32		49		0.01	3.11	
1/17/2000		3210			3.7		4.0		7.7		7.7					155		157			23		53		0.00	3.11	
1/18/2000		3160			3.9		4.2		7.7		7.7					152		156			29		43		0.07	3.18	
1/19/2000		3200			4.0		4.8		7.7		7.7					142		152			32		47		0.10	3.28	
1/20/2000		3430			4.3		4.8		7.7		7.7					142		150			30		56		0.00	3.28	
1/21/2000		3460			4.1		4.5		7.7		7.8					143		146			27		50		0.01	3.29	
1/22/2000		3580			4.2		4.5		7.8		7.8					142		145			31		52		0.00	3.29	
1/23/2000		3540			4.3		4.6		7.8		7.8					139		143			30		54		0.01	3.30	
1/24/2000		3440			4.4		4.6		7.8		7.8					141		144			35		45		0.05	3.35	
1/25/2000		3190			4.3		4.7		7.8		7.8					143		144			27		54		0.00	3.35	
1/26/2000		3120			4.4		4.7		7.8		7.8					142		144			26		48		0.00	3.35	
1/27/2000		3090			4.0		4.4		7.8		7.8					142		144			20		50		0.00	3.35	
1/28/2000		3070			3.9		4.4		7.8		7.8					144		146			18		50		0.00	3.35	
1/29/2000		3060			4.0		4.5		7.8		7.8					146		147			19		50		0.00	3.35	
1/30/2000		3080			4.3		4.5		7.8		7.8					147		148			28		47		0.04	3.39	
1/31/2000		3100			4.3		4.5		7.8		7.8					148		150			28		41		0.00	3.39	
2/1/2000		3080			4.4		4.8		7.8		7.8					148		150			36		55		0.00	3.39	
2/2/2000		3160			4.3		4.8		7.8		7.8					148		150			28		59		0.00	3.39	
2/3/2000		3150			4.4		4.8		7.8		7.8					149		152			27		64		0.00	3.39	
2/4/2000		3180			4.3		4.7		7.8		7.8					152		153			27		49		0.00	3.39	
2/5/2000		3170			4.5		4.8		7.8		7.8					151		169			33		54		0.00	3.39	
2/6/2000		3170			4.4		4.8		7.8		7.8					155		157			29		61		0.00	3.39	
2/7/2000		3160			4.4		5.0		7.8		7.8					156		159			23		67		0.00	3.39	
2/8/2000		3160			4.5		4.8		7.8		7.8					158		159			31		56		0.00	3.39	
2/9/2000		3160			4.5		5.1		7.8		7.8					155		158			27		60		0.00	3.39	
2/10/2000		3160			4.7		5.2		7.8		7.8					156		157			36		59		0.03	3.42	
2/11/2000		3180			4.8		5.1		7.8		7.8					156		158			31		47		0.01	3.43	
2/12/2000		3180			4.8		5.1		7.7		7.8					156		158			32		52		0.01	3.44	
2/13/2000		3230			4.9		5.2		7.7		7.8					156		164			36		53		0.08	3.52	
2/14/2000		3780			5.1		5.5		7.7		7.8					162		179			36		47		0.11	3.63	
2/15/2000		4220			5.0		5.5		7.7		7.8					164		176			29		50		0.00	3.63	
2/16/2000		4750			5.3		5.7		7.7		7.8					161		168			34		52		0.00	3.63	
2/17/2000		4660			5.6		6.1		7.7		7.8					159		169			28		55		0.03	3.66	
2/18/2000		4440			5.5		6.1		7.7		7.8					157		160			23		57		0.00	3.66	
2/19/2000		4010			5.6		6.3		7.7		7.8					155		157			20		60		0.00	3.66	
2/20/2000		3810			6.1		6.3		7.7		7.8					154		159									

KLAMATH R BL IRON GATE DAM CA
 DISCHARGE, CUBIC FEET PER SECOND; TEMPERATURE, WATER (DEG. C); PH, WATER, WHOLE, FIELD, STANDARD UNITS;
 OXYGEN DISSOLVED (MG/L);SPECIFIC CONDUCTANCE (MICROSIEMENS/CM AT 25 DEG. C); TEMPERATURE, AIR, DEGREES FAHRENHEIT
 START="19991001" END "20000930"

DATE	DC	MEAN	BOR	MIN	WT	MIN	WT	MAX	pH	MIN	pH	MAX	DO	MIN	DO	MAX	CON	MIN	CON	MAX	AT	MIN	AT	MAX	ACCUM	
																									PRECIP	PRECIP
2/27/2000		4510			6.2	7.1			7.7		7.8						155	170			36	49	0.12	4.12		
2/28/2000		4370			6.0	6.7			7.7		7.7						155	172			33	52	0.00	4.12		
2/29/2000		4370			6.1	6.7			7.7		7.7						154	164			28	49	0.06	4.18		
3/1/2000		4200			5.8	6.5			7.7		7.7						148	166			23	49	0.00	4.18		
3/2/2000		4010			6.3	6.6			7.7		7.7						145	149			31	50	0.03	4.21		
3/3/2000		3950			5.9	6.3			7.6		7.7						145	150			27	61	0.00	4.21		
3/4/2000		4020			6.1	6.6			7.6		7.7						140	153			33	45	0.14	4.35		
3/5/2000		4170			5.6	6.3			7.6		7.7						144	155			32	38	0.04	4.39		
3/6/2000		4070			5.9	6.6			7.3		7.8						144	146			29	48	0.00	4.39		
3/7/2000		4710			5.9	6.3			7.7		7.7		12.8		13.2		144	150			28	47	0.00	4.39		
3/8/2000		5060			6.0	6.4			7.7		7.7		12.7		13.2		148	152			31	51	0.00	4.39		
3/9/2000		4710			6.0	6.5			7.7		7.7		12.7		13.1		151	154			29	51	0.00	4.39		
3/10/2000		4660			6.0	6.4			7.7		7.7		12.7		13.2		152	155			27	60	0.00	4.39		
3/11/2000		4650			6.1	6.8			7.7		7.8		12.8		13.2		153	155			30	57	0.00	4.39		
3/12/2000		4510			5.9	6.6			7.7		7.7		12.9		13.3		153	154			24	60	0.00	4.39		
3/13/2000		4680			6.1	6.5			7.7		7.7		13.1		13.3		153	154			30	58	0.00	4.39		
3/14/2000		4690			6.1	6.9			7.7		7.8		12.9		13.2		154	157			30	64	0.00	4.39		
3/15/2000		4530			6.2	7.0			7.7		7.8		12.6		13.2		156	159			25	69	0.00	4.39		
3/16/2000		4000			6.5	7.6			7.7		7.8		12.5		13.0		156	160			34	51	0.00	4.39		
3/17/2000		3510			6.4	7.3			7.7		7.8		12.3		12.7		160	161			24	57	0.00	4.39		
3/18/2000		3380			6.8	7.3			7.7		7.8		12.1		12.5		160	161			35	58	0.01	4.40		
3/19/2000		3390			7.1	7.8			7.7		7.8		12.0		12.3		161	162			34	50	0.00	4.40		
3/20/2000		3380			6.7	7.8			7.7		7.8		12.0		12.3		160	161			25	56	0.00	4.40		
3/21/2000		3360			6.9	8.1			7.7		7.8		11.7		12.3		160	160			25	80	0.00	4.40		
3/22/2000		2950			7.5	8.4			7.7		7.7		11.5		11.9		158	160			32	68	0.02	4.42		
3/23/2000		2810			7.7	8.6			7.7		7.8		11.5		11.8		158	159			28	59	0.00	4.42		
3/24/2000		2730			7.5	8.6			7.7		7.7		11.2		11.7		158	159			24	68	0.00	4.42		
3/25/2000		2770			7.9	9.1			7.7		7.8		11.0		11.5		158	159			30	70	0.00	4.42		
3/26/2000		2910			8.3	9.4			7.7		7.8		10.8		11.4		159	159			26	74	0.00	4.42		
3/27/2000		2720			8.4	10.0			7.7		7.8		10.8		11.3		159	160			35	60	0.00	4.42		
3/28/2000		2580			8.1	9.5			7.7		7.8		10.1		10.9		160	161			26	54	0.00	4.42		
3/29/2000		2590			8.0	9.7			7.7		7.8		8.3		10.8		160	162			24	72	0.00	4.42		
3/30/2000		2580			8.6	9.9			7.7		7.8		8.6		10.8		161	163			34	76	0.00	4.42		
3/31/2000		2580			8.5	10.0			7.7		7.8		9.8		10.5		161	166			29	81	0.00	4.42		
4/1/2000		2590	2200		9.0	10.6			7.7		7.8		9.8		10.6		157	165			33	77	0.00	4.42		
4/2/2000		2590	2200		9.3	10.9			7.7		7.8		7.3		10.2		163	164			34	84	0.00	4.42		
4/3/2000		2590	2200		9.7	10.0			7.7		7.9		8.9		11.2		161	164			35	85	0.00	4.42		
4/4/2000		2600	2200		9.8	11.7			7.7		7.9		9.0		9.7		161	162			39	78	0.00	4.42		
4/5/2000		2550	2200		10.3	11.9			7.7		8.0		9.4		9.9		160	162			33	74	0.00	4.42		
4/6/2000		2270	2200		10.3	12.1			7.7		8.0		9.3		10.3		160	161			31	66	0.00	4.42		
4/7/2000		2230	2200		10.5	12.1			7.7		7.8		9.5		10		160	162			32	78	0.00	4.42		
4/8/2000		2220	2200		10.8	11.9			7.6		7.8		8.9		9.9		160	164			40	71	0.00	4.42		
4/9/2000		2220	2200		10.8	12.7			7.6		8.0		9.2		10.5		160	164			37	66	0.00	4.42		
4/10/2000		2220	2200		11.3	12.4			7.7		7.9		9.4		9.9		162	164			32	75	0.00	4.42		
4/11/2000		2220	2200		11.5	12.3			7.6		7.8		9.1		10.1		159	162			37	78	0.00	4.42		
4/12/2000		2230	2200		11.3	12.6			7.6		7.9		9.1		10.3		156	159			45	70	0.05	4.47		
4/13/2000		2280	2200		11.5	12.5			7.6		7.8		9.5		10.1		154	156			44	59	0.16	4.63		
4/14/2000		2300	2200		11.8	12.6			7.5		7.7		9.2		10.1		154	158			42	63	0.02	4.65		
4/15/2000		2310	2200		11.6	12.1			7.5		7.6		8.5		9.9		154	157			41	51	0.09	4.74		
4/16/2000		2290	2200		11.2	11.9			7.4		7.6		9.3		10.0		152	155			38	59	0.01	4.75		
4/17/2000		2280	2200		11.4	12.1			7.4		7.6		9.6		10.3		151	152			39	60	0.08	4.83		
4/18/2000		2580	2200		10.8	11.6			7.4		7.5		9.3		10.1		151	164			37	44	0.16	4.99		
4/19/2000		2500	2200		10.8	11.8			7.4		7.5		9.0		9.7		157	168			41	58	0.00	4.99		
4/20/2000		2380	2200		10.9	12.4			7.3		7.5		9.6		10.1		152	157			38	75	0.00	4.99		
4/21/2000		2390	2200		11.0	12.9			7.4		7.6		9.8		10.6		151	152			36	77	0.00	4.99		
4/22/2000		3060	2200		11.7	13.3			7.4		7.7		9.9		10.9		145	152			43	69	0.00	4.99		
4/23/2000		3680	2200		11.3	12.4			7.4		7.6		10.2		10.8		150	152			35	56	0.00	4.99		
4/24/2000		3930	2200		11.1	12.1			7.4		7.5		10.0		10.6		152	154			28	67	0.00	4.99		
4/25/2000		3770	2200		11.5	12.9			7.4		7.7		10.1		10.8		153	156			39	66	0.00	4.99		
4/26/2000		3190	1750		11.3	12.7			7.3		7.6		9.7		10.4		155	158			37	80	0.00	4.99		
4/27/2000		2490	1750		11.4	12.0			7.2		7.5		9.3		10.3		157	159			37	70	0.03	5.02		
4/28/2000		2360	1750		10.9	12.0			7.3		7.6		9.9		11.2		158	160			29	51	0.00	5.02		
4/29/2000		2380	1750		10.7	12.5			7.4		7.7		10.9		11.7		158	160			27	69	0.00	5.02		
4/30/2000		2300	1750		11.5	13.4			7.5		7.9		11.5		12.6		158	160			33	83	0.00	5.02		
5/1/2000		2450	1750		12.3	13.0			7.6		7.9		12.1		12.8		156	160			36	80	0.02	5.04		
5/2/2000		2560	1750		11.9	13.4			7.6		7.9		12.5		13.2		153	157			37	75	0.00	5.04		
5/3/2000		2580	1750		12.7	13.7			7.5		7.9		12.4		13.3		151	154			45	71	0.00	5.04		
5/4/2000		2580	1750		12.8	14.4			7.6		8.0		12.1		13.4		148	152			40	64	0.01	5.05		
5/5/2000		2560	1750		12.5	14.2			7.6		8.0		11.9		13.1		146	148			32	69	0.00	5.05		
5/6/2000																										

KLAMATH R BL IRON GATE DAM CA
 DISCHARGE, CUBIC FEET PER SECOND; TEMPERATURE, WATER (DEG. C); PH, WATER, WHOLE, FIELD, STANDARD UNITS;
 OXYGEN DISSOLVED (MG/L);SPECIFIC CONDUCTANCE (MICROSIEMENS/CM AT 25 DEG. C); TEMPERATURE, AIR, DEGREES FAHRENHEIT
 START="19991001" END "20000930"

DATE	DC	MEAN	BOR	MIN	WT	MIN	WT	MAX	pH	MIN	pH	MAX	DO	MIN	DO	MAX	CON	MIN	CON	MAX	AT	MIN	AT	MAX	ACCUM	
																									PRECIP	PRECIP
5/16/2000	2260	1750	12.4	14.3	7.2	7.6	9.2	10.7	150	153	44	63	0.01	5.14												
5/17/2000	2250	1750	13.0	14.7	7.2	7.4	9.4	10.4	152	154	43	67	0.00	5.14												
5/18/2000	2220	1750	13.0	14.5	7.2	7.3	9.4	9.9	152	153	36	80	0.00	5.14												
5/19/2000	1870	1750	13.3	15.5	7.1	7.3	9.4	10.3	153	156	43	81	0.00	5.14												
5/20/2000	1810	1750	13.5	15.6	7.1	7.4	9.4	10.3	156	159	41	87	0.00	5.14												
5/21/2000	1810	1750	13.8	16.1	7.1	7.3	9.3	10.4	158	162	44	92	0.00	5.14												
5/22/2000	1810	1750	14.3	16.9	7.1	7.5	9.2	11.0	160	163	50	88	0.00	5.14												
5/23/2000	1800	1750	14.4	17.9	7.1	7.6	9.1	11.2	163	165	49	85	0.00	5.14												
5/24/2000	1800	1750	14.7	18.1	7.1	7.6	9.4	11.0	163	166	45	79	0.00	5.14												
5/25/2000	1800	1750	14.9	17.5	7.2	7.9	9.6	10.5	164	169	43	82	0.00	5.14												
5/26/2000	1800	1750	14.9	16.1	7.3	7.7	8.3	9.6	169	178	47	81	0.00	5.14												
5/27/2000	1800	1750	15.6	17.0	7.4	7.7	8.5	9.5	176	179	55	83	0.00	5.14												
5/28/2000	1800	1750	15.6	17.7	7.4	7.7	8.7	9.5	177	179	46	76	0.00	5.14												
5/29/2000	1810	1750	15.6	17.9	7.3	7.6	8.8	9.3	177	182	38	68	0.00	5.14												
5/30/2000	1810	1750	16.3	17.9	7.1	7.5	8.6	9.7	181	187	36	58	0.00	5.14												
5/31/2000	1810	1750	15.5	17.2	7.0	7.2	8.4	9.3	186	191	30	74	0.00	5.14												
6/1/2000	1630	1500	15.5	17.0	7.0	7.2	8.0	9.0	191	199	34	87	0.00	5.14												
6/2/2000	1590	1500	16.0	17.8	7.0	7.2	8.1	8.9	199	204	42	87	0.00	5.14												
6/3/2000	1580	1500	16.5	17.7	7.0	7.2	8.3	9.0	203	207	41	91	0.00	5.14												
6/4/2000	1560	1500	15.9	17.9	7.0	7.3	7.8	9.1	200	208	44	87	0.00	5.14												
6/5/2000	1530	1500	16.0	18.5	7.0	7.3	7.5	9.2	202	211	43	80	0.00	5.14												
6/6/2000	1530	1500	17.0	18.0	7.1	7.6	8.4	9.3	207	211	41	82	0.00	5.14												
6/7/2000	1540	1500	17.1	17.6	7.4	7.7	7.7	9.1	206	212	45	77	0.06	5.20												
6/8/2000	1540	1500	16.9	18.0	7.3	7.7	7.6	8.4	206	211	46	60	0.01	5.21												
6/9/2000	1540	1500	16.7	17.4	7.4	7.6	6.8	8.3	206	211	44	69	0.00	5.21												
6/10/2000	1540	1500	16.7	18.4	7.4	7.7	6.9	8.2	210	214	40	64	0.00	5.21												
6/11/2000	1540	1500	16.7	17.4	7.3	7.6	6.8	8.3	210	212	38	71	0.00	5.21												
6/12/2000	1540	1500	16.6	17.3	7.3	7.5	6.9	8.2	208	214	50	74	0.00	5.21												
6/13/2000	1540	1500	16.7	19.1	7.3	7.7	7.1	8.5	210	215	43	95	0.00	5.21												
6/14/2000	1530	1500	17.5	19.4	7.4	7.8	7.0	8.7	211	215	51	93	0.00	5.21												
6/15/2000	1530	1500	17.5	19.7	7.5	7.8	7.3	8.8	212	217	55	85	0.00	5.21												
6/16/2000	1420	1000	17.6	19.5	7.5	7.8	7.2	8.7	216	219	46	84	0.00	5.21												
6/17/2000	1270	1000	18.0	19.3	7.5	7.7	7.2	8.6	216	219	55	91	0.00	5.21												
6/18/2000	1280	1000	17.4	19.8	7.4	7.8	7.3	8.7	214	218	48	91	0.00	5.21												
6/19/2000	1220	1000	17.8	19.6	7.4	7.7	7.2	8.7	214	217	47	81	0.00	5.21												
6/20/2000	1040	1000	17.7	19.9	7.4	7.7	7.1	8.8	215	217	46	92	0.00	5.21												
6/21/2000	1050	1000	18.1	20.3	7.4	7.7	7.2	9.1	213	217	50	94	0.00	5.21												
6/22/2000	1050	1000	18.6	20.6	7.5	7.9	7.4	9.1	213	216	53	87	0.00	5.21												
6/23/2000	1050	1000	18.5	20.6	7.6	7.9	7.8	9.7	209	214	50	87	0.00	5.21												
6/24/2000	1050	1000	18.6	21.1	7.6	7.9	7.7	9.9	209	212	50	88	0.00	5.21												
6/25/2000	1070	1000	18.6	20.8	7.5	7.9	7.2	9.5	209	218	50	93	0.00	5.21												
6/26/2000	1060	1000	19.2	21.2	7.5	8.0	7.3	9.7	208	216	53	99	0.00	5.21												
6/27/2000	1050	1000	18.9	20.6	7.6	8.0	7.6	9.8	207	214	51	98	0.00	5.21												
6/28/2000	1040	1000	19.1	21.6	7.7	8.1	7.7	10.1	204	208	52	94	0.00	5.21												
6/29/2000	1050	1000	19.2	21.2	7.7	8.0	8.2	10.2	200	205	53	97	0.00	5.21												
6/30/2000	1050	1000	19.3	21.8	7.6	8.2	7.9	10.2	201	204	54	85	0.00	5.21												
7/1/2000	1050	1000	19.2	21.8	7.8	8.3	7.8	10.6	198	204	50	78	0.00	5.21												
7/2/2000	1050	1000	19.1	21.2	7.8	8.2	8.0	10.4	195	199	39	78	0.00	5.21												
7/3/2000	1040	1000	19.0	21.1	7.8	8.3	8.1	10.8	196	198	44	70	0.00	5.21												
7/4/2000	1040	1000	18.8	20.1	7.7	8.2	8.5	10.7	191	197	33	75	0.00	5.21												
7/5/2000	1040	1000	18.7	19.6	7.6	8.1	8.3	10.7	192	195	47	69	0.00	5.21												
7/6/2000	1040	1000	18.2	19.8	7.6	7.8	8.3	10.9	194	198	39	77	0.00	5.21												
7/7/2000	1040	1000	18.4	19.5	7.5	7.7	8.4	10.8	194	199	49	82	0.00	5.21												
7/8/2000	1050	1000	18.4	20.1	7.5	7.8	8.9	10.9	193	196	43	80	0.00	5.21												
7/9/2000	1060	1000	18.8	20.6	7.6	7.8	8.9	11.1	192	195	48	83	0.00	5.21												
7/10/2000	1060	1000	18.8	19.7	7.6	8.0	7.5	10.7	191	195	46	88	0.00	5.21												
7/11/2000	1060	1000	19.0	20.5	7.6	7.9	7.4	9.1	189	194	50	94	0.00	5.21												
7/12/2000	1050	1000	19.2	20.3	7.6	7.9	7.1	9.4	187	190	53	94	0.00	5.21												
7/13/2000	1050	1000	19.0	20.1	7.6	7.9	7.4	9.5	185	189	51	88	0.00	5.21												
7/14/2000	1050	1000	19.2	20.9	7.6	8.1	6.7	9.6	183	190	49	87	0.00	5.21												
7/15/2000	1050	1000	19.2	20.2	7.6	8.0	7.3	9.5	183	188	55	92	0.00	5.21												
7/16/2000	1050	1000	19.3	20.3	7.7	8.1	7.4	9.7	182	186	56	92	0.00	5.21												
7/17/2000	1050	1000	19.3	20.6	7.6	8.2	6.4	9.9	181	186	62	91	0.00	5.21												
7/18/2000	1050	1000	19.3	20.7	7.7	8.1			180	194	55	91	0.00	5.21												
7/19/2000	1050	1000	19.4	20.9	7.6	8.2			184	191	52	94	0.00	5.21												
7/20/2000	1050	1000	19.6	20.8	7.6	8.2			183	188	52	98	0.00	5.21												
7/21/2000	1060	1000	19.7	20.8	7.6	8.1	6.6	9.1	179	186	56	96	0.00	5.21												
7/22/2000	1060	1000	19.7	21.7	7.6	8.2	5.8	8.7	179	183	55	84	0.00	5.21												
7/23/2000	1060	1000	19.6	21.3	7.6	8.0	6.5	8.7	178	182	50	94	0.00	5.21												
7/24/2000	1060	1000	19.7	21.5	7.7	8.0	5.8	8.1	179	182	53	95	0.00	5.21												
7/25/2000	1060	1000	19.6	21.8	7.6	8.2	5.3	8.7	177	196	51	88	0.00	5.21												
7/26/2000	1060	1000	19.5	21.7	7.7	8.3	6.3	8.7	173	181	50	88	0.00	5.21												
7/27/2000	1060	1000	19.6	21.1	7.7	8.1	5.9	8.4	173	177	51	93	0.00	5.21												
7/28/2000	1060	1000	19.8	21.7	7.8	8.2	5.7	8.3	174	183	54	97	0.00	5.21												
7/29/2000	1050	1000	20.0	21.6	7.8	8.1	5.9	8.1	177	184	55	99	0.00	5.21												
7/30/2000	1050	1000	20.2	21.7	7.8	8.2	6.7	8.7	174	181	58	99	0.00	5.21												
7/31/2000	1060	1000	20.4	22.6	7.8	8.5	6.9	9.2	173	176	60	95	0.00	5.21												
8/1/2000	1060	1000	20.4	22.1	7.8	8.3	6.5	8.7	174	178	57	102	0.00	5.21												
8/2/2000	1060	1000	20.5	21.8	7.8	8.2	6.4	8.2	175	178	55	106	0.00	5.21												

KLAMATH R BL IRON GATE DAM CA
 DISCHARGE, CUBIC FEET PER SECOND; TEMPERATURE, WATER (DEG. C); PH, WATER, WHOLE, FIELD, STANDARD UNITS;
 OXYGEN DISSOLVED (MG/L);SPECIFIC CONDUCTANCE (MICROSIEMENS/CM AT 25 DEG. C); TEMPERATURE, AIR, DEGREES FAHRENHEIT
 START="19991001" END "20000930"

DATE	DC MEAN	BOR MIN	WT MIN	WT MAX	pH MIN	pH MAX	DO MIN	DO MAX	CON MIN	CON MAX	AT MIN	AT MAX	ACCUM	
													PRECIP	PRECIP
8/3/2000	1060	1000	20.7	21.5	7.9	8.2	5.2	8.0	175	180	58	99	0.00	5.21
8/4/2000	1060	1000	20.4	21.5	7.7	8.2	6.3	7.9	179	185	56	97	0.00	5.21
8/5/2000	1060	1000	20.5	22.0	7.8	8.6	6.1	8.6	178	185	56	99	0.00	5.21
8/6/2000	1060	1000	20.6	22.2	8.0	8.7	6.9	8.5	178	182	55	97	0.00	5.21
8/7/2000	1060	1000	20.7	22.1	8.2	8.6	6.1	8.5	175	180	54	100	0.00	5.21
8/8/2000	1060	1000	20.6	20.7	8.0	8.4			174	187	63	98	0.00	5.21
8/9/2000	1060	1000	20.1	21.7	7.6	8.5			172	176	61	99	0.00	5.21
8/10/2000	1060	1000	20.2	21.6	7.7	8.7			172	184	51	91	0.00	5.21
8/11/2000	1060	1000	20.5	21.6	8.3	8.7			178	196	49	92	0.00	5.21
8/12/2000	1060	1000	20.7	22.0	8.2	8.8			196	215	49	94	0.00	5.21
8/13/2000	1060	1000	20.5	21.9	7.9	8.6					47	93	0.00	5.21
8/14/2000	1060	1000	20.5	21.8	7.7	8.2					47	90	0.00	5.21
8/15/2000	1060	1000	20.3	21.8	7.7	8.2					47	86	0.00	5.21
8/16/2000	1060	1000	20.4	21.6	7.6	8.4					46	91	0.00	5.21
8/17/2000	1060	1000	20.3	21.8	7.8	8.6					47	84	0.00	5.21
8/18/2000	1060	1000	20.1	21.4	7.8	8.6					44	80	0.00	5.21
8/19/2000	1060	1000	20.0	21.4	7.6	8.0					48	80	0.00	5.21
8/20/2000	1060	1000	20.1	21.2	7.6	7.9					45	82	0.00	5.21
8/21/2000	1080	1000	20.0	21.0	7.6	8.0					46	92	0.00	5.21
8/22/2000	1080	1000	19.7	20.0	7.4	8.1					48	94	0.00	5.21
8/23/2000	1080	1000	19.4	20.5	7.5	8.6					45	99	0.00	5.21
8/24/2000	1080	1000	19.3	20.5	7.5	8.4					48	91	0.00	5.21
8/25/2000	1080	1000	19.6	20.8	7.2	7.8					45	93	0.00	5.21
8/26/2000	1080	1000	19.9	21.0	6.6	7.2					51	90	0.00	5.21
8/27/2000	1080	1000	20.0	21.1	6.6	6.9					49	95	0.00	5.21
8/28/2000	1080	1000	19.8	20.7	6.6	6.8					48	96	0.00	5.21
8/29/2000	1080	1000	19.9	21.2	6.7	6.9					49	94	0.00	5.21
8/30/2000	1080	1000	19.6	20.8	6.8	7.0					49	88	0.00	5.21
8/31/2000	1080	1000	19.5	20.6	7.0	7.2					49	83	0.00	5.21
9/1/2000	1080	1300	19.2	20.2	6.9	7.0					52	68	0.01	5.22
9/2/2000	1080	1300	18.6	19.2	6.9	7.0					46	68	0.00	5.22
9/3/2000	1080	1300	18.4	19.2	7.0	7.1					39	69	0.00	5.22
9/4/2000	1090	1300	18.3	18.9	7.1	7.2					44	70	0.06	5.28
9/5/2000	1090	1300	18.1	19.1	7.2	7.2					46	69	0.00	5.28
9/6/2000	1090	1300	18.0	19.1	7.2	7.4					40	81	0.00	5.28
9/7/2000	1120	1300	17.9	19.0	7.4	7.4					40	90	0.00	5.28
9/8/2000	1350	1300	18.1	19.0	7.4	7.7					43	81	0.00	5.28
9/9/2000	1350	1300	18.0	18.7	7.5	7.6					40	83	0.00	5.28
9/10/2000	1350	1300	17.8	18.9	7.6	7.8					41	86	0.00	5.28
9/11/2000	1350	1300	18.0	18.9	7.7	7.9			176	199	49	104	0.00	5.28
9/12/2000	1350	1300	18.1	18.9	7.6	7.9	4.8	7.8	178	180	49	96	0.00	5.28
9/13/2000	1330	1300	17.9	18.9	7.6	7.8	4.8	5.7	177	180	52	92	0.00	5.28
9/14/2000	1310	1300	17.7	18.4	7.5	7.7	4.0	5.7	176	179	52	89	0.00	5.28
9/15/2000	1310	1300	17.7	18.8	7.5	7.7	4.1	6.1	177	179	50	84	0.00	5.28
9/16/2000	1310	1300	18.0	19.5	7.5	7.8	5.1	6.6	178	180	48	75	0.00	5.28
9/17/2000	1310	1300	17.9	19.2	7.5	7.7	5.2	6.3	176	180	46	90	0.00	5.28
9/18/2000	1320	1300	17.8	19.6	7.4	7.7	5.3	6.4	176	178	48	102	0.00	5.28
9/19/2000	1310	1300	18.2	19.7	7.3	7.6	5.3	6.2	175	178	54	98	0.00	5.28
9/20/2000	1300	1300	18.7	19.4	7.3	7.7	5.3	7.0	176	177	61	99	0.00	5.28
9/21/2000	1300	1300	18.1	19.5	7.4	7.7	5.7	7.2	175	177	48	77	0.00	5.28
9/22/2000	1310	1300	17.8	18.6	7.3	7.5	5.7	7.1	175	176	51	68	0.00	5.28
9/23/2000	1310	1300	17.1	17.8	7.2	7.4	5.5	6.7	174	176	40	72	0.00	5.28
9/24/2000	1310	1300	16.5	17.4	7.1	7.3	4.8	5.7	176	178	30	82	0.00	5.28
9/25/2000	1310	1300	16.6	17.4	7.1	7.2	5.0	6.0	175	178	33	84	0.00	5.28
9/26/2000	1310	1300	16.6	17.4	7.1	7.2	4.8	5.9	176	178	36	85	0.00	5.28
9/27/2000	1310	1300	16.6	17.4	7.0	7.1			176	179	38	87	0.00	5.28
9/28/2000	1310	1300	16.8	18.0	7.0	7.2			174	178	44	84	0.00	5.28
9/29/2000	1320	1300	16.7	17.9	6.9	7.1			176	179	42	83	0.00	5.28
9/30/2000	1320	1300	16.6	17.9	6.9	7.0			178	181	43	86	0.00	5.28