

KLAMATH R NEAR SEIAD VALLEY
 DISCHARGE, CUBIC FEET PER SECOND; TEMPERATURE, WATER (DEG. C); PH, WATER, WHOLE, FIELD, STANDARD UNITS;
 OXYGEN DISSOLVED (MG/L);SPECIFIC CONDUCTANCE (MICROSIEMENS/CM AT 25 DEG. C); TEMPERATURE, AIR, DEGREES FAHRENHEIT
 START="19991001" END "20000930"

DATE	DC MEAN	WT MIN	WT MAX	pH MIN	pH MAX	DO MIN	DO MAX	CON MIN	CON MAX	AT MIN	AT MAX
10/1/1999	1670										
10/2/1999	1690										
10/3/1999	1690										
10/4/1999	1700										
10/5/1999	1690										
10/6/1999	1710										
10/7/1999	1730										
10/8/1999	1710										
10/9/1999	1700										
10/10/1999	1710										
10/11/1999	1700										
10/12/1999	1690										
10/13/1999	1670										
10/14/1999	1720										
10/15/1999	1710										
10/16/1999	1690										
10/17/1999	1700										
10/18/1999	1680										
10/19/1999	1680										
10/20/1999	1680										
10/21/1999	1700										
10/22/1999	1700										
10/23/1999	1700										
10/24/1999	1690										
10/25/1999	1690										
10/26/1999	1710										
10/27/1999	1790										
10/28/1999	2090										
10/29/1999	2170										
10/30/1999	2240										
10/31/1999	2220										
11/1/1999	2200										
11/2/1999	2180										
11/3/1999	2180										
11/4/1999	2170										
11/5/1999	2180										
11/6/1999	2180										
11/7/1999	2350										
11/8/1999	2370										
11/9/1999	2370										
11/10/1999	2570										
11/11/1999	2510										
11/12/1999	2490										
11/13/1999	2440										
11/14/1999	2390										
11/15/1999	2370										
11/16/1999	2390										
11/17/1999	2410										
11/18/1999	2370										
11/19/1999	2410										
11/20/1999	2460										
11/21/1999	2360										
11/22/1999	2290										
11/23/1999	2280										
11/24/1999	2270										
11/25/1999	2280										
11/26/1999	2390										
11/27/1999	2450										
11/28/1999	2400										
11/29/1999	2390										
11/30/1999	2660										
12/1/1999	2800										
12/2/1999	2830										
12/3/1999	2750										
12/4/1999	2640										
12/5/1999	2560										

KLAMATH R NEAR SEIAD VALLEY

DISCHARGE, CUBIC FEET PER SECOND; TEMPERATURE, WATER (DEG. C); PH, WATER, WHOLE, FIELD, STANDARD UNITS;
 OXYGEN DISSOLVED (MG/L);SPECIFIC CONDUCTANCE (MICROSIEMENS/CM AT 25 DEG. C); TEMPERATURE, AIR, DEGREES FAHRENHEIT
 START="19991001" END "20000930"

DATE	DC MEAN	WT MIN	WT MAX	pH MIN	pH MAX	DO MIN	DO MAX	CON MIN	CON MAX	AT MIN	AT MAX
12/6/1999	2530										
12/7/1999	2610										
12/8/1999	2600										
12/9/1999	2600										
12/10/1999	2560									30	36
12/11/1999	2540									34	41
12/12/1999	2570									35	41
12/13/1999	2680										
12/14/1999	2640										
12/15/1999	2590									32	40
12/16/1999	2560									34	41
12/17/1999	2550										
12/18/1999	2590									30	47
12/19/1999	2580									29	44
12/20/1999	2590									30	47
12/21/1999	2590										
12/22/1999	2570									29	44
12/23/1999	2540									26	46
12/24/1999	2520										
12/25/1999	2520										
12/26/1999	2510									26	44
12/27/1999	2500										
12/28/1999	2490									24	36
12/29/1999	2480									26	36
12/30/1999	2480									26	35
12/31/1999	2470										
1/1/2000	2610										
1/2/2000	2470										
1/3/2000	2470										
1/4/2000	2490									30	42
1/5/2000	2480										
1/6/2000	2460	3.5	4.5	7.9	8			217	218	25	37
1/7/2000	2450			7.9	8			216	218	32	42
1/8/2000	2460			7.9	8.1			216	217	34	46
1/9/2000	2470	5	5.5	7.9	8			215	216	37	41
1/10/2000	2910	5	6	7.8	7.9			178	215	37	43
1/11/2000	6270	5	6	7.8	7.8			178	196	31	44
1/12/2000	6040	4.5	5	7.8	7.9			192	231	29	36
1/13/2000	5740	3.5	4.5	7.9	7.9			219	227	29	31
1/14/2000	8390	4.5	5.5	7.8	7.9			191	219	30	35
1/15/2000	9300	5.5	5.5	7.8	7.8			188	202	32	38
1/16/2000	8980	5.5	6	7.8	7.8			191	201	33	37
1/17/2000	7660	5	5.5	7.8	7.8			193	209	30	36
1/18/2000	6450	4.5	5	7.8	7.9			209	212	32	38
1/19/2000	6110	5	6	7.9	7.9			212	214	36	41
1/20/2000	6770	5.5	6	7.9	8			204	212	35	42
1/21/2000	6550	5.5	5.5	7.9	7.9			204	208	33	40
1/22/2000	6340	5	5.5	7.9	7.9			203	206	33	41
1/23/2000	6050	5.5	5.5	7.8	7.9			200	203	34	38
1/24/2000	5970	5.5	6	7.8	7.8			198	200	37	42
1/25/2000	5870	6	6	7.8	7.9			196	198	38	45
1/26/2000	5630	6	6.5	7.5	7.9			196	200	31	43
1/27/2000	5360	5	6	7.6	7.8			197	198	28	40
1/28/2000	5150	4.5	5	7.7	7.8			196	198	26	43
1/29/2000	4980	4.5	4.5	7.7	7.7			196	198	26	41
1/30/2000	4920	4.5	5.5	7.7	7.8			193	197	27	42
1/31/2000	4920	5	5.5	7.7	7.8			194	196	33	37
2/1/2000	4920	5.5	6	7.6	7.7			192	198	36	46
2/2/2000	5080	6	6.5	7.6	7.6			185	193	37	47
2/3/2000	5050	6	6	7.6	7.6			183	188	35	56
2/4/2000	5040	6	6	7.6	7.7			182	184	33	46
2/5/2000	5010	6	6.5	7.6	7.7			180	183	37	45
2/6/2000	5100	6	6	7.5	7.6			181	186	37	47
2/7/2000	5010	5.5	6	7.6	7.6			181	185	34	46
2/8/2000	4910	6	6.5	7.6	7.6			184	188	36	44
2/9/2000	4880	6	6.5	7.6	7.6			184	189	39	51

KLAMATH R NEAR SEIAD VALLEY

DISCHARGE, CUBIC FEET PER SECOND; TEMPERATURE, WATER (DEG. C); PH, WATER, WHOLE, FIELD, STANDARD UNITS;
 OXYGEN DISSOLVED (MG/L);SPECIFIC CONDUCTANCE (MICROSIEMENS/CM AT 25 DEG. C); TEMPERATURE, AIR, DEGREES FAHRENHEIT
 START="19991001" END "20000930"

DATE	DC MEAN	WT MIN	WT MAX	pH MIN	pH MAX	DO MIN	DO MAX	CON MIN	CON MAX	AT MIN	AT MAX
2/10/2000	4870	6.5	7	7.6	7.6			185	190	41	49
2/11/2000	4930	6.5	7	7.6	7.6			179	185	39	44
2/12/2000	4990	6.5	6.5	7.5	7.6			176	180	37	44
2/13/2000	5120	6	6.5	7.5	7.5			171	176	33	41
2/14/2000	7750	6	6.5	7.5	7.7			168	174	36	42
2/15/2000	9360	6	6.5	7.7	7.9			172	204	34	44
2/16/2000	8380	6.5	7	7.8	7.9			205	245	37	48
2/17/2000	7840	6.5	7.5	7.9	8			246	300	34	47
2/18/2000	7370	6.5	7	7.9	8			300	330	31	46
2/19/2000	6760	6	6.5	7.8	7.9			330	365	28	46
2/20/2000	6260	6.5	7.5	7.8	7.9			365	398	33	53
2/21/2000	6110	7	8	7.8	7.9			399	411	38	49
2/22/2000	6140	6.5	7.5	7.9	7.9			411	414	34	39
2/23/2000	7080	6	6.5	7.9	7.9			408	414	31	40
2/24/2000	6840	6	6.5	7.8	7.9			364	408	31	41
2/25/2000	6490	6.5	7	7.8	7.9			311	363	34	44
2/26/2000	7100	6.5	7	7.8	7.8			301	311	30	39
2/27/2000	8800	7	7.5	7.8	7.8			229	301	38	45
2/28/2000	9200	7	7.5	7.8	7.8			217	229	36	46
2/29/2000	8790	7	7.5	7.8	7.9			224	249	33	42
3/1/2000	8400	6.5	7.5	7.9	7.9			249	269	33	45
3/2/2000	7740	7	7.5	7.9	7.9			257	276	35	45
3/3/2000	7340	7	8	7.9	7.9			244	269	34	52
3/4/2000	7130	7	8	7.9	7.9			230	244	35	43
3/5/2000	8080	6.5	7	7.9	7.9			221	237	34	40
3/6/2000	7860	6.5	7.5	7.9	7.9			206	221	34	44
3/7/2000	7670	6.5	7	7.9	8			200	208	34	45
3/8/2000	8050	6.5	7	8	8	10.8	11.3	196	200	33	46
3/9/2000	7650	6.5	7	8	8	11.2	11.4	196	199	33	44
3/10/2000	7400	6.5	7	8	8	11.1	11.5	195	198	34	40
3/11/2000	7200	7	8	8	8	11.1	11.4	195	197	31	46
3/12/2000	6950	7	8	8	8	10.9	11.6	194	196	29	53
3/13/2000	6960	7	8	7.9	8	10.8	11.6	193	196	34	49
3/14/2000	7060	7.5	9	7.9	8	11.1	11.5	193	194	34	53
3/15/2000	7060	7	8.5	7.9	8	10.9	11.6	192	194	29	56
3/16/2000	6730	8.5	9	7.9	8	10.6	11	193	196	32	50
3/17/2000	6290	7.5	8.5	7.9	8	10.5	11.3	194	198	28	54
3/18/2000	5950	8	8.5	7.9	8	10.2	10.8	198	199	36	49
3/19/2000	6120	8.5	9	7.9	8	10.2	10.7	194	199	34	46
3/20/2000	6180	7.5	8.5	7.9	8	10.7	11.3	193	194	30	52
3/21/2000	5970	7.5	9	7.9	8.1	10.2	11.2	194	195	29	62
3/22/2000	5720	8.5	9.5	8	8.1	9.9	10.7	194	197	36	62
3/23/2000	5410	9	9.5	8	8.1	9.9	10.5	195	198	33	53
3/24/2000	5380	8.5	9.5	8	8.1	9.8	10.6	195	197	27	58
3/25/2000	5210	9	10.5	8	8.1	9.5	10.2	197	199	33	60
3/26/2000	5310	9.5	11	8	8.1	9.4	10.3	196	198	34	62
3/27/2000	5330	10	10.5	8	8.1	9.3	10.1	196	198	35	50
3/28/2000	5070	9	10	8	8.2	9.3	10.1	196	198	29	51
3/29/2000	4930	9	10	8.1	8.2	9.2	10.1	197	200	28	58
3/30/2000	4830	9	10.5	8.1	8.2	8.9	9.9	200	202	29	62
3/31/2000	4730	9.5	11	8	8.2	8.7	9.6	201	203	32	67
4/1/2000	4720	10	12	8	8.2	8.5	9.4	200	203	36	72
4/2/2000	4820	11	12.5	8	8.2	8.4	9.6	194	201	38	75
4/3/2000	5100	11.5	13	8	8.2	8.8	10.1	189	194	38	78
4/4/2000	5600	11.5	12	7.8	8	9.1	12.4	175	189	38	69
4/5/2000	5810	11	12	7.7	7.9	12.4	14.1	172	175	36	66
4/6/2000	5390	11	12	7.5	7.7	13.1	14.3	173	177	35	65
4/7/2000	4930	11	12.5	7.5	7.6	12.8	14.3	176	180	35	72
4/8/2000	4870	11.5	12.5	7.5	7.6	12.8	14.2	174	179	39	63
4/9/2000	4950	11	12.5	7.4	7.6	13.8	15.3	171	174	39	62
4/10/2000	4780	11.5	13	7.4	7.5	13.6	15.1	173	176	24	69
4/11/2000	4740	12	13.5	7.3	7.4	13.6	15.2	172	176	40	72
4/12/2000	4910	12	13	7.2	7.4	14	15.5	160	172	48	56
4/13/2000	6310	11	12	7.3	7.3	15.4	17.8	142	160	44	52
4/14/2000	6610	10.5	11.5	7.3	7.3	9.9	17.3	147	221	43	57
4/15/2000	5850	11	12	7.2	7.3	8	12.7	188	249	41	53

KLAMATH R NEAR SEIAD VALLEY

DISCHARGE, CUBIC FEET PER SECOND; TEMPERATURE, WATER (DEG. C); PH, WATER, WHOLE, FIELD, STANDARD UNITS;
 OXYGEN DISSOLVED (MG/L);SPECIFIC CONDUCTANCE (MICROSIEMENS/CM AT 25 DEG. C); TEMPERATURE, AIR, DEGREES FAHRENHEIT
 START="19991001" END "20000930"

DATE	DC MEAN	WT MIN	WT MAX	pH MIN	pH MAX	DO MIN	DO MAX	CON MIN	CON MAX	AT MIN	AT MAX
4/16/2000	5750	10.5	11.5	7.2	7.4	12.7	13.9	176	188	38	57
4/17/2000	5650	11	11.5	7.3	7.4	10.7	13.8	174	209	39	58
4/18/2000	6160	10	10.5	7.2	7.4	11.1	14.9	166	201	35	43
4/19/2000	6490	10	11	7.3	7.4	12	14	173	188	40	54
4/20/2000	5950	11	13	7.3	7.4	11.2	12.3	187	191	44	63
4/21/2000	5770	12.5	13.5	7.3	7.3	10.8	12.1	186	194	42	68
4/22/2000	6170	12.5	13.5	7.3	7.4	10.5	12	178	195	38	54
4/23/2000	6710	11.5	13	7.3	7.4	11.9	13.3	167	178	34	53
4/24/2000	7030	11	12.5	7.3	7.4	12.5	13.3	166	170	31	59
4/25/2000	6870	12	13.5	7.2	7.4	12.2	13.5	160	170	39	57
4/26/2000	6390	12	14	7.3	7.4	11.9	13.2	162	165	37	68
4/27/2000	5750	12	13.5	7.2	7.3	11.7	12.9	159	165	37	59
4/28/2000	5280	11	12	7.3	7.4	11.9	12.7	164	169	32	48
4/29/2000	5130	10	12.5	7.2	7.3	11.7	12.9	160	165	30	63
4/30/2000	4860	12	14	7.2	7.3	11.1	12.3	162	167	37	72
5/1/2000	4860	13	14	7.2	7.3	11.8	11.9	161	167	39	65
5/2/2000	5160	12.5	14	7.2	7.3	12.1	12.3	156	160	46	66
5/3/2000	5350	13	14	7.2	7.3	11.2	11.9	154	160	45	61
5/4/2000	5330	13	13.5	7.2	7.3	11	12.8	144	157	38	59
5/5/2000	5160	12.5	13.5	7.2	7.3	11.2	12.8	144	152	41	57
5/6/2000	4950	12.5	13	7.2	7.3	11	12.1	146	153	40	55
5/7/2000	5100	12.5	13	7.3	7.3	8.2	11	152	193	42	55
5/8/2000	5210	13	14.5	7.1	7.3	7.7	9.3	171	203	47	62
5/9/2000	5190	13.5	14.5	7.1	7.2	9.2	10.8	161	171	42	53
5/10/2000	5090	12	13.5	7.1	7.7	9.1	10.9	158	171	33	43
5/11/2000	5010	11.5	13	7.2	7.6	9.5	10.7	160	163	36	51
5/12/2000	4940	12	13	7.2	7.6	9.3	10.6	163	166	34	57
5/13/2000	4650	12.5	13	7.2	7.6	9.2	10.2	166	170	42	57
5/14/2000	4200	12	13.5	7.3	7.6	9	10.1	170	172	42	62
5/15/2000	4020	12.5	13	7.3	7.6	9	10.1	172	175	40	56
5/16/2000	4070	12.5	14.5	7.2	7.7	8.6	10.1	173	177	44	65
5/17/2000	4060	13.5	16	7.3	7.8	8.5	10	175	177	41	66
5/18/2000	4060	14	16	7.2	7.8	8.5	10.2	174	177	40	74
5/19/2000	3930	15	17	7.3	7.8	8.4	10.2	172	177	45	78
5/20/2000	3850	15	17.5	7.3	7.8	8.4	10.1	169	175	45	82
5/21/2000	4050	15	18	7.3	7.8	8.7	10.6	162	170	47	86
5/22/2000	4440	15.5	17.5	7.2	7.6	8.9	10.5	158	165	48	79
5/23/2000	4630	15.5	18.5	7.2	7.7	9.2	10.6	153	158	51	82
5/24/2000	4900	15.5	17.5	7.3	7.5	9.5	11.3	140	154	49	77
5/25/2000	4750	15.5	17	7.3	7.5	10.1	11.2	142	149	48	68
5/26/2000	4420	15	17.5	7.3	7.6	9.6	10.9	148	155	52	72
5/27/2000	4400	15.5	16.5	7.3	7.5	9.5	10.4	155	158	52	64
5/28/2000	4350	15	17	7.3	7.6	9.6	10.7	152	159	46	66
5/29/2000	4060	14	16.5	7.4	7.7	9.4	10.9	152	161	39	66
5/30/2000	3840	15	16.5	7.4	7.7	8.9	10.3	161	172	40	58
5/31/2000	3650	14	16.5	7.4	7.9	8.5	9.9	171	181	35	68
6/1/2000	3440	14.5	18	7.5	7.9	8	9.5	176	185	39	77
6/2/2000	3200	16	19	7.5	7.9	7.8	9.2	181	189	44	79
6/3/2000	3200	16	19.5	7.5	8	7.7	9.3	184	190	44	82
6/4/2000	3260	17	20	7.5	8	7.7	9.2	183	188	46	81
6/5/2000	3210	16.5	19	7.5	7.9	7.8	9.5	178	185	46	68
6/6/2000	3100	16	18.5	7.4	7.8	7.5	9.4	176	186	46	71
6/7/2000	3060	16.5	18	7.3	7.5			176	187	50	66
6/8/2000	3230	15.5	17	7.5	7.6			187	201	46	60
6/9/2000	3280	15	16.5	7.5	7.6			199	232	43	59
6/10/2000	3110	15	17.5	7.4	7.5			222	234	45	60
6/11/2000	2950	15	17	7.5	7.5			212	237	40	64
6/12/2000	2910	15.5	18	7.4	7.5			213	223	51	65
6/13/2000	2980	16	19.5	7.4	7.4			203	214	46	82
6/14/2000	2950	18	21.5	7.4	7.5			198	208	51	87
6/15/2000	2930	19	22	7.4	7.4			193	205	54	82
6/16/2000	2900	18.5	21	7.4	7.5			193	205	49	81
6/17/2000	2570	18	21.5	7.4	7.5			186	199	47	85
6/18/2000	2410	18.5	22	7.4	7.4			188	222	50	82
6/19/2000	2320	19	21.5	7.4	7.6			194	217	49	76
6/20/2000	2120	18.5	22	7.4	7.5			194	204	47	86

KLAMATH R NEAR SEIAD VALLEY

DISCHARGE, CUBIC FEET PER SECOND; TEMPERATURE, WATER (DEG. C); PH, WATER, WHOLE, FIELD, STANDARD UNITS;
 OXYGEN DISSOLVED (MG/L);SPECIFIC CONDUCTANCE (MICROSIEMENS/CM AT 25 DEG. C); TEMPERATURE, AIR, DEGREES FAHRENHEIT
 START="19991001" END "20000930"

DATE	DC MEAN	WT MIN	WT MAX	pH MIN	pH MAX	DO MIN	DO MAX	CON MIN	CON MAX	AT MIN	AT MAX
6/21/2000	1990	19.5	23	7.5	7.5			197	202	53	89
6/22/2000	1920	20.5	23.5	7.5	7.7			188	203	55	84
6/23/2000	1860	20.5	23.5	7.5	7.6			190	198	52	83
6/24/2000	1820	20.5	23	7.5	7.6			188	195	52	85
6/25/2000	1760	20.5	23.5	7.4	7.5			188	195	52	88
6/26/2000	1720	21	24	7.4	7.5			189	196	55	90
6/27/2000	1670	21	24	7.5	7.5			188	203	51	90
6/28/2000	1610	21.5	24.5	7.5	7.6			187	196	53	90
6/29/2000	1560	21.5	24.5	7.5	7.6			187	206	54	89
6/30/2000	1540	22	24	7.5	7.7			189	206	55	83
7/1/2000	1500	21	23.5	7.7	7.7			186	193	53	75
7/2/2000	1490	20.5	23	7.7	7.7			180	194	48	76
7/3/2000	1470	20	22	7.6	7.7			180	189	47	70
7/4/2000	1470	19	21.5	7.6	7.6			181	189	44	65
7/5/2000	1500	18.5	19.5	7.6	7.6			178	184	51	61
7/6/2000	1560	17.5	20.5	7.6	7.6			178	206	51	71
7/7/2000	1550	18.5	20.5	7.6	7.6			182	202	49	75
7/8/2000	1540	18	21.5	7.6	7.6			184	221	47	75
7/9/2000	1530	19.5	22.5	7.5	7.6			186	261	49	80
7/10/2000	1480	20	23	7.5	7.5			245	264	48	83
7/11/2000	1440	20.5	23.5	7.5	7.9			223	245	51	86
7/12/2000	1420	21.5	24	7.3	7.9	6	7.9	222	227	53	85
7/13/2000	1400	21.5	24	7.3	7.9	6	7.9	221	226	51	82
7/14/2000	1370	21	23.5	7.3	7.9	6.1	8	217	226	51	81
7/15/2000	1360	21	24	7.3	7.9	6.1	8.2	215	222	53	84
7/16/2000	1350	21.5	23.5	7.3	7.8	6.1	8	216	220	54	79
7/17/2000	1360	21	24	7.2	7.9	6	8.1	212	229	61	83
7/18/2000	1350	21	23.5	7.3	7.9	6.2	8.4	212	220	51	81
7/19/2000	1330	21	24	7.3	7.9	6.4	8.6	208	218	49	85
7/20/2000	1300	21.5	24.5	7.2	7.9	6.4	9.2	199	214	52	88
7/21/2000	1300	22.5	25	7.2	7.9	6.6	9.5	195	208	56	86
7/22/2000	1300	22	24	7.2	8	7	9.3	190	203	55	81
7/23/2000	1290	21.5	24.5	7.3	8.1	6.6	9.8	190	201	53	85
7/24/2000	1270	22	25	7.3	8.1	6.3	8.8	188	198	54	88
7/25/2000	1260	21.5	24	7.3	8	6.2	9.8	184	192	51	83
7/26/2000	1260	21	23.5	7.3	8	6.2	9.6	181	189	50	80
7/27/2000	1250	21	24	7.3	8	6.9	9.9	182	189	51	84
7/28/2000	1230	22	25	7.3	8.1	7.2	10.4	175	186	55	87
7/29/2000	1230	22.5	25.5	7.2	8	7.7	10.7	173	180	57	90
7/30/2000	1210	23.5	26	7.2	8	7.6	10.6	174	181	60	91
7/31/2000	1220	23.5	26.5	7.1	7.9	7.7	11	166	178	61	91
8/1/2000	1210	23.5	26	7.1	7.9	8.1	11.1	166	172	57	93
8/2/2000	1210	23.5	26	7.2	8	8.2	11	165	173	57	94
8/3/2000	1200	23.5	25.5	7.2	8	7.9	11.2	161	171	56	91
8/4/2000	1190	22.5	25	7.3	7.9	8.6	11.4	161	168	54	89
8/5/2000	1190	22.5	25	7.2	8	8	10.7	163	183	55	90
8/6/2000	1200	22.5	25	7.2	7.9	7.8	10.4	179	185	54	90
8/7/2000	1210	23	25.5	7.1	7.8	7.8	10.8	172	185	55	92
8/8/2000	1210	23.5	26	7.1	7.8	7.3	10.8	173	195	61	90
8/9/2000	1190	23.5	26	7.1	7.4			195	232	58	86
8/10/2000	1190	22.5	24	7.4	7.5			214	233	52	80
8/11/2000	1190	21	23.5	7.4	7.5			215	230	49	82
8/12/2000	1180	21	24	7.4	7.4			201	231	50	85
8/13/2000	1180	21.5	24	7.3	7.4			198	203	50	81
8/14/2000	1180	21	23.5	7.3	7.5			202	208	47	82
8/15/2000	1180	21	24	7.4	7.5			207	211	48	81
8/16/2000	1180	21	23.5	7.4	7.4			204	214	47	85
8/17/2000	1180	21	23.5	7.4	7.4			204	209	49	80
8/18/2000	1180	20.5	23	7.4	7.5			208	216	49	76
8/19/2000	1180	20	22.5	7.5	7.5			196	212	47	75
8/20/2000	1180	20	22.5	7.5	7.5			193	196	47	77
8/21/2000	1190	20	23	7.5	7.5			193	197	48	84
8/22/2000	1210	21	23.5	7.5	7.6			193	202	45	86
8/23/2000	1230	21.5	23.5	7.6	7.7			196	210	51	85
8/24/2000	1250	21	23	7.6	7.7			196	201	50	83
8/25/2000	1240	20.5	23	7.6	7.8			196	208	50	84

KLAMATH R NEAR SEIAD VALLEY

DISCHARGE, CUBIC FEET PER SECOND; TEMPERATURE, WATER (DEG. C); PH, WATER, WHOLE, FIELD, STANDARD UNITS;
 OXYGEN DISSOLVED (MG/L);SPECIFIC CONDUCTANCE (MICROSIEMENS/CM AT 25 DEG. C); TEMPERATURE, AIR, DEGREES FAHRENHEIT
 START="19991001" END "20000930"

DATE	DC MEAN	WT MIN	WT MAX	pH MIN	pH MAX	DO MIN	DO MAX	CON MIN	CON MAX	AT MIN	AT MAX
8/26/2000	1230	20.5	23	7.8	7.8			199	206	50	84
8/27/2000	1230	21	23.5	7.8	7.8			200	211	51	86
8/28/2000	1220	21	23.5	7.8	7.8			203	209	51	87
8/29/2000	1200	21	23.5	7.8	7.9			196	204	50	88
8/30/2000	1200	21	23	7.9	7.9			194	199	52	83
8/31/2000	1210	20.5	22.5	7.9	7.9			196	200	51	76
9/1/2000	1210	19	21	7.9	8			197	199	46	61
9/2/2000	1240	18	19	8	8.1			194	198	44	57
9/3/2000	1260	17	19	8	8.1			194	195	44	60
9/4/2000	1280	17.5	20	8	8.1			192	194	44	65
9/5/2000	1290	17	19.5	8	8.1			192	197	40	66
9/6/2000	1290	17.5	20	8.1	8.1			196	213	41	73
9/7/2000	1300	18	20.5	8.1	8.1			213	231	44	78
9/8/2000	1410	19	20.5	8.1	8.2			210	234	48	73
9/9/2000	1550	18	20.5	8.1	8.3			198	210	42	75
9/10/2000	1540	18	20.5	8.2	8.3			188	201	44	78
9/11/2000	1550	18.5	21.5	8.2	8.3			186	190	50	82
9/12/2000	1560	20	22.5	7.8	8.3			186	211	52	83
9/13/2000	1580	20	22	7.4	7.9			202	210	56	85
9/14/2000	1520	19	21.5	7.3	7.4			200	206	54	71
9/15/2000	1510	19	20.5	7.3	7.4			200	210	60	72
9/16/2000	1510	18.5	21	7.2	7.4			210	233	51	73
9/17/2000	1500	18.5	21	7.2	7.2			233	245	48	81
9/18/2000	1490	19	21.5	7.1	7.2			241	245	50	86
9/19/2000	1510	19.5	22	6.9	7.1			239	243	54	86
9/20/2000	1490	19.5	21.5	6.9	6.9			239	243	54	84
9/21/2000	1490	19	21	6.8	6.9			231	242	51	78
9/22/2000	1490	18	20	6.8	6.8			224	231	46	69
9/23/2000	1470	16.5	19	6.7	6.8			204	224	41	68
9/24/2000	1470	15	17.5	6.6	6.8			200	204	35	70
9/25/2000	1460	15	17.5	6.6	6.6			198	201	38	72
9/26/2000	1460	15.5	18	6.5	6.6			198	200	40	75
9/27/2000	1450	15.5	18	6.5	6.6			198	200	41	74
9/28/2000	1450	16	18.5	6.6	6.8			198	200	47	76
9/29/2000	1440	16.5	18.5	6.6	6.8			198	201	46	77
9/30/2000	1440	16.5	19	6.6	6.7			200	205	46	77